



DT-200 SERIES

ADVANCED DIGITAL THEODOLITE





All The Theodolite You'll Ever Need

- Laser pointer through the scope
- Extremely low power consumption
- Waterproof and dustproof
- RS232C data I/O port
- Operates on 4 AA batteries

Make your next job a snap

With Topcon's DT-200 you'll be up and working fast, thanks to its simple interface and large, easy-to-see backlit LCD. There's an optical plummet that makes set up over a control point easy, and a tilt sensor that provides ± 3 minute angle correction. The DT-200 Series features two magnification choices – 26x and 30x, a super-short 3 ft. minimum focus distance for those tight areas, and angle accuracies of 5, 7, and 9 arc seconds.

Laser pointer

Add a whole new dimension of accuracy and confidence to your alignment jobs with Topcon's unique DT-200L Series featuring a red Class II laser beam. Use it anywhere on your site and see clearly in direct sunlight up to 165 ft. Now you can easily and accurately place anchor bolts at regular intervals on a line, set an angle and use the beam to verify your tape measure is properly aligned for the next stake, or "sight in" footers, frames, and tilt-up walls.

The ultimate in continuous operation

The DT-200/DT-200L Series provides up to 170 hours of operation in Angle Measurement mode on 4 AA batteries, better than any other model. When it is time to change batteries, it's as easy as snapping out the old ones and snapping in the new. When using the laser, power consumption is low, providing up to 45 hours of continuous operation.



Durability, accuracy, and value

Topcon's DT-200 Series represents the highest accuracy and value in digital theodolite technology. Only Topcon, with over 80 years of experience manufacturing the world's most precise optical survey instruments can offer the precision, durability, and advanced technology found in each DT-200.



Model	DT-205 DT-205L	DT-207 DT-207L	DT-209 DT-209L
Angle Measurement Accuracy	5"	7"	9"
Telescope Magnification	30x	30x	26x
Laser Pointer	Focusing (DT-205L)	Focusing (DT-207L)	Focusing (DT-209L)
Display Unit	2 sides	2 sides	1 side
Compensator Tilt Sensor	Vertical	N/A	N/A
Compensating Range	±3'	N/A	N/A
Operating Temperature	-20°C to 50°C		
Operating Time: Theodolite Only	140 hours	150 hours	170 hours
Operating Time: Theodolite and Laser	45 hours (DT-205L)	45 hours (DT-207L)	45 hours (DT-209L)

Kit components

- Instrument
- Plumb bob
- Tool kit
- Lint free lens cloth
- Hard shell carry case



Water and dustproof

- IP66 rating
- Treated telescope to prevent moisture and eliminate lens fogging
- Rain proof
- Dust proof



Laser accurate (L Series Only)

- Beam is emitted directly from the lens
- Bright red laser
- Pin-point accuracy



Simple Operation

- Large, high-contrast, back-lit LCD's
- Simple five button interface panel
- Horizontal and vertical angles
- Slope by percent on angle



Fast, reliable data gathering

(DT-205/205L)

- Output horizontal angles
- Output vertical angles
- Connects to PC
- Cable connection



For more information:
topconpositioning.com/dt-200

Specifications subject to change without notice.
 ©2016 Topcon Corporation All rights reserved.
 7010-0630 G 2/16